



## MULTI-PURPOSE ATF

### DESCRIPTION:

**Multi-Purpose ATF** is an automatic transmission fluid that has been created for electronically controlled transmissions. This product may be used in GM automatic transmission units that require the use of DEXRON® IIIH, DEXRON® IIIG, DEXRON® IIE, DEXRON® IID, DEXRON® II, and DEXRON® fluids; and is a qualified Ford MERCON® ATF. Further, it meets the performance requirements for Allison Transmission Division (C-4), and major hydraulic pump manufacturers' requirements for antiwear hydraulic fluids. **Multi-Purpose ATF** provides excellent friction stability, oxidation, anti-wear properties, and low-temperature fluidity desired for most automatic transmissions.

### FEATURES/BENEFITS:

- Excellent cold temperature performance
- Provides a wide range of seal compatibility, not harmful to synthetic rubber seals
- Provides excellent wear protection and good lubrication properties
- Possesses excellent frictional characteristics for smoother shifting and quieter operation
- Prevents rust and oxidation
- Provides foaming resistance – contains an anti-foaming agent
- Dye red for easy identification

### APPLICATIONS:

**Multi-Purpose ATF** is a premium lubricant for both truck and car automatic transmissions and also other applications which require an automatic transmission fluid satisfying either General Motor's DEXRON III-H or Ford's MERCON ATF specifications. **Multi-Purpose ATF** meets the transmission fluid requirements for Allison automatic transmissions and other heavy duty equipment that requires a DEXRON® III fluid. It is approved against the Allison C-4 specification, TES 389 specification, and can be used in Allison Powershift transmissions or other torque converter systems that specify this type of fluid.

### Meets the following OEM requirements:

- General Motor's DEXRON® III-H
- Ford's MERCON®
- Allison C-4
- Allison TES 389
- Type A Suffix A
- Type CJ

\* ALWAYS CONSULT YOUR OWNER'S MANUAL FOR THE PROPER FLUID FOR YOUR EQUIPMENT.

### TYPICAL TEST DATA

Product Specifications	Results
Specific Gravity @ 60°F	0.8590
Viscosity, Kinematic	

# **PREFERRED**

## *Lubricants*

---

cSt at 100°C	7.0
Viscosity, Kinematic cSt at 40°C	32.2
Viscosity Index	188
Viscosity, Brookfield cP at -40°C Max	20,000
Flash Point, (°F) Min	350
Pour Point, °C (°F)	-48 (-54)
Color	Red

Typical test data are average values only. Minor variations which do not affect product performance are to be expected during normal manufacturing.