



## CNG Synthetic Blend SAE 15w40

### DESCRIPTION:

**Synthetic Blend SAE 15W40 CNG Engine Oil** is specially blended for use in engines operating in severe service applications using Compressed Natural Gas (CNG) or Liquefied Natural Gas (LNG). **Synthetic Blend SAE 15W40 CNG Engine Oil** is recommended for use in a wide range of heavy duty applications and operating environments found in the trucking and bus transportation industry.

### FEATURES/BENEFITS:

- Excellent protection against oxidation and nitration
- Protection against wear and deposits
- Low zinc and phosphorous content
- Superior detergency

### APPLICATIONS:

**Synthetic Blend SAE 15W40 CNG Engine Oil** is recommended for North American and European mobile engines fueled with CNG/LNG. Can be used globally and where long drain applications are required.

### Meets Performance Requirements:

- CUMMINS CES 20074
- CUMMINS CES 20085
- DETROIT DIESEL 93K216

\* ALWAYS CONSULT YOUR OWNER'S MANUAL FOR THE PROPER FLUID FOR YOUR EQUIPMENT.

### TYPICAL TEST DATA

SAE GRADE	15W40
Specific Gravity @ 60 °F	0.8697
Viscosity, Kinematic cSt at 40°C cSt at 100°C	98.7 13.6
Viscosity Index	138
Cold Crank, cP at °C, Max	7000 @ -20C
Flash Point, °F	436
Pour Point, °C (°F)	-21 (-6)
Color, Max	4.0
TBN	7
Sulfated Ash, wt%	0.89
Phosphorus, ppm	799
Zinc, ppm	920

Typical test data are average values only. Minor variations which do not affect product performance are to be expected during normal manufacturing.