



## ROCK DRILL 150

### DESCRIPTION:

**Rock Drill 150** is designed to give maximum protection to percussion rock drills. It has been specially formulated from highly refined, high viscosity index, paraffinic base stocks and select additives in order to provide the necessary characteristics expected in superior rock drill oils. **Rock Drill 150** provides exceptional corrosion and rust protection and is not easily washed off by incidental water from compressed air.

### FEATURES/BENEFITS:

- Extreme pressure properties help extend equipment life
- Protects equipment against accelerated wear and tear
- Rust inhibitors protect parts in wet environments
- Multipurpose lubricant can be used for gears, air tools, and chain drives
- Contains additives which provide unusual adhesion and tackiness

### APPLICATIONS:

**Rock Drill 150** has proven to be excellent in all air-operated tools in a variety of environments. It also performs well in enclosed gears, and both plain and anti-friction bearings.

\* ALWAYS CONSULT YOUR OWNER'S MANUAL FOR THE PROPER FLUID FOR YOUR EQUIPMENT.

### TYPICAL TEST DATA

ISO GRADE	150
Specific Gravity @ 60 °F	0.9207
Viscosity, Kinematic cSt at 40°C Min/Max cSt at 100°C	135.0 – 165.0 11.3
Viscosity Index	44
Flash Point, °F	394
Pour Point, °C (°F)	-25 (-13)
Color	2.5
Tackifier	PRESENT

Typical test data are average values only. Minor variations which do not affect product performance are to be expected during normal manufacturing.