



BAR AND CHAIN OIL

DESCRIPTION:

Bar and Chain Oil is formulated with premium base stocks and highly effective additives to help achieve optimum performance as a chain saw bar and chain lubricant. **Bar and Chain Oil** is formulated to resist dripping and throw-off. It protects the bar, chain and sprocket against wear and prevents rusting and reduces friction and heat build-up on cutting chain and guide bar. **Bar and Chain Oil** can be used at a wide range of temperature, and maintains superior performance in cold weather. For extremely cold weather, consult your operator's manual.

FEATURES/BENEFITS:

- Extends bar, chain and sprocket life
- Reduces wear and prevents rust
- Resists dripping
- Superior low temperature performance

APPLICATIONS:

Bar and Chain Oil is recommended for all makes of chain saws and all types of link chains that require lubrication, including motorcycles, and bicycles, as well as farm and industrial uses.

Hazards:

Contains Petroleum Distillates. Use with adequate ventilation. Keep away from heat, flame and all other sources of ignition. Avoid prolonged contact with skin. In case of contact, wash thoroughly with soap and water. Do not take internally. If swallowed, do not induce vomiting. Call physician or Poison Control Center immediately. Keep out of reach of children.

* ALWAYS CONSULT YOUR OWNER'S MANUAL FOR THE PROPER FLUID FOR YOUR EQUIPMENT.

TYPICAL TEST DATA

Product Specifications	Results
Specific Gravity, (60°F)	0.9130
Kinematic Viscosity, cSt at 40°C cSt at 100°C	135.6 11.1
Viscosity Index	52
Flash Point, (°F)	385
Pour Point, °C (°F)	-30 (-22)
Color, Max	2.5
Tac	Present

Typical test data are average values only. Minor variations which do not affect product performance are to be expected during normal manufacturing.

PREFERRED 
Lubricants
