



FLEET SAE 30

DESCRIPTION:

Fleet SAE 30 Motor Oil provides high quality engine protection under all driving conditions and is specifically formulated to provide extra protection against the harmful effects of city driving.

Fleet SAE 30 Motor Oil low friction formula helps improve gas mileage, extend engine life and helps protect against rust, corrosion, startup wear and varnish build-up. It also protects against thermal breakdown which helps prevent stuck rings.

FEATURES/BENEFITS:

- Protects engines under all driving conditions
- Lowers friction and improves gas mileage
- Provides longer engine life
- Protects against rust, corrosion, and varnish
- Resists thermal break-down

APPLICATIONS:

- On the highway applications for light and heavy-duty trucking
- Off the highway applications such as trucking, construction, agriculture, and quarrying
- Various mixed fleet applications

May be Suitable for Use in applications where the following are indicated:

- API CH-4, CF, CD, CC
- API SL, SJ, SG, SF
- MAN 270
- MB 228.2
- MTU Category 2

* ALWAYS CONSULT YOUR OWNER'S MANUAL FOR THE PROPER FLUID FOR YOUR EQUIPMENT.

TYPICAL TEST DATA

SAE GRADE	30
Specific Gravity @ 60 °F	0.8956
Viscosity, Kinematic cSt at 40°C	87.6
cSt at 100°C	10.4
Viscosity Index	102
Flash Point, °F	405
Pour Point, °C (°F)	-29 (-20)

PREFERRED

Lubricants

Color, Max	4.5
TBN	8.5

Typical test data are average values only. Minor variations which do not affect product performance are to be expected during normal manufacturing.