



DESCRIPTION:

TO-4 Fluid SAE 10 is a high performance transmission and drive-train lubricant designed to meet the requirements of Caterpillar’s TO-4 specifications. **TO-4 Fluid SAE 10** is engineered to optimize the performance of powershift transmissions, gearboxes, and final drives. **TO-4 Fluid SAE 10** contains an advanced additive system to deliver the precise performance parameters needed to maximize the productivity of construction, quarrying, and mining equipment operating in severe conditions

FEATURES/BENEFITS:

- Designed for heavy-duty construction equipment power shift transmissions
- Special additives protect metal surfaces against scuffing and wear
- Frictional controls stop slippage and assure silent and efficient action
- Resists oxidation at elevated operating temperatures
- Defends against rust and corrosion of highly refined precision parts
- Base oils and additives are carefully chosen for compatibility with clutch face and seal materials

APPLICATIONS:

- **TO-4 Fluid SAE 10** is compatible with new and traditional seal and clutch material, and heavy duty off highway automatic transmissions.

Meets Performance Requirements:

- API MT-1
- CATERPILLAR TO-4
- ALLISON C-4
- KOMATSU KES 07.868.1 (2002)
- ZF TE-ML-03C, ZF TE-ML-07F

* ALWAYS CONSULT YOUR OWNER’S MANUAL FOR THE PROPER FLUID FOR YOUR EQUIPMENT.

TYPICAL TEST DATA

SAE GRADE	10
Specific Gravity @ 60 °F	0.8727
Viscosity, Kinematic	
cSt at 40°C	26.5
cSt at 100°C	5.0
Viscosity Index	113
Flash Point, °F	405
Pour Point, °C (°F)	-39 (-38)
Color	<3.0

Typical test data are average values only. Minor variations which do not affect product performance are to be expected during normal manufacturing.