



FS Global ATF

Description:

Lubricants Full Synthetic Global ATF is formulated from premium synthetic base stocks and a state-of-the-art additive system to provide ultimate protection and peak performance in automatic transmissions found in passenger cars, flex-fuel vehicles, hybrids, light-trucks, and sport utility vehicles.

Features and Benefits:

- Formulated with synthetic base stocks for increased lubricity and shear stability
- Effective anti-wear chemistry; protects against pre-mature wear
- Advanced anti-oxidant additive technology; reduced sludge and deposits
- Enhanced frictional characteristics

Applications:

- Bentley P/N PY112995PA
- BMW / MINI ATF-3+
- Chrysler / Dodge / Jeep MB236.12
- Mercedes / Daimler MB 236.12, MB 236.14, MB 236.15, MB 236.41
- Ford / Lincoln / Mercury MERCON® LV & MERCON® SP
- GM / GMC / Opel / Saturn AW1, DEXRON® VI
- Honda / Acura DW-1, ATF Type 3.0, ATF Type 3.1
- Hyundai / Kia NWS-9638 T-5, SP-IV/SPH-IV, SP-IV-RR
- Jaguar Fluid 8432
- Mazda FW 6A EL, FW 6AX EL, FZ
- Mitsubishi ATF-J3, Dia Queen ATF-PA
- Nissan / Infinity Matic-S
- Porsche P/N 000 043 304 00
- Toyota / Lexus / Scion FZ, Type WS (JWS 3324)
- Volkswagen / Audi G 052 533, G 055 005 (-A, A2), G 055 540 (A2), G 060 162 (A1, A2, A6)
- Multiple OEMs Shell 3353, 134, M-1375.4, L12108, ZF Lifeguardfluid6, ZF Lifeguardfluid8



Typical Physical Properties

Property	Test Method	
Viscosity @ 40°C, cSt	ASTM D445	27.3
Viscosity @ 100°C, cSt	ASTM D445	5.7
Viscosity Index	ASTM D2270	158
Flash Point, °C (°F)	ASTM D92	184 (363)
Pour Point, °C (°F)	ASTM D97	-54 (-65)
Brookfield Visc. @ -40°C, cP	ASTM D2983	8,006
Copper Corrosion @ 100°C	ASTM D130	1B
Foam Stability	ASTM D892	PASS