

# ROCK DRILL 100

## DESCRIPTION

Rock Drill 100 is designed to give maximum protection to percussion rock drills. It has been specially formulated from highly refined, high viscosity index, paraffinic base stocks and select additives in order to provide the necessary characteristics expected in superior rock drill oils. XL Rock Drill 100 provides exceptional corrosion and rust protection and are not easily washed off by incidental water from compressed air.

## APPLICATIONS

Rock Drill 100 has proven to be excellent in all air-operated tools in a variety of environments. It also performs well in enclosed gears, and both plain and anti-friction bearings.

## BENEFITS

- Extreme pressure properties help extend equipment life
- Protects equipment against accelerated wear and tear
- Rust inhibitors protect parts in wet environments
- Multipurpose lubricant can be used for gears, air tools, and chain drives
- Contains additives which provide unusual adhesion and tackiness

# ROCK DRILL 100

*\*Always consult your owners manual for the proper fluid for your equipment.*

## TYPICAL PHYSICAL PROPERTIES

SAE GRADE	15W40
Specific Gravity @ 60 °F	0.8763
Viscosity, Kinematic cSt at 40 °C Min/Max cSt at 100 °C	90.0 – 110.0 11.0
Viscosity Index	107
Flash Point, °F	400
Pour Point, °C (°F)	-12 (10)
Color	< 3.0
Tackifier	PRESENT

Typical test data are average values only. Minor variations which do not affect product performance are to be expected during normal manufacturing.